

# SANYO LCD PROJECTORS

## MODEL :PLC-XW55A/50A series



- ◇ XW55:2000 lm, XW50:1500 lm
- ◇ D-sub 15pin for Input, D-sub 15pin for Monitor out
- ◇ AC plug out right after Power off, 16 languages (Operation menu)
- ◇ Keystone Correction $\uparrow\downarrow$ : $\pm 20$ deg, Black board (for Green color) mode
- ◇ Security : PIN code lock, Key lock

TENTATIVE

Model name	SANYO PLC-XW55A/50A series
Panel	0.6 inch TFT p-Si x 3 with Micro Lens
No. of pixels	2,359,296 (1024x768 dots)
Projection lamp	200W UHP
Expectation of lamp life	(Life Survival ratio 50%, Maintenance integral 40%) Normal : 2000H, Eco : 3000H
Brightness (typical)	XW55 : 2000 lm / XW50 : 1500 lm
Contrast	No Announce (400:1 for Auto Lamp mode & Dynamic Image mode)
Uniformity	85% (corner to center)
Projection lens	F1.7, f=20.06 mm
Screen size	40" ~ 300", 1.31~ 9.9 (m) 100" at 3.3m
Zoom / Focus	Fixed U:D = 6:1
Approximate calculation	y=30.142x + 0.5987 y : screen size (inch), x : throw distance (m)
HDTV signals	480i, 480p, 575i, 575p, 720p, 1035i and 1080i
Color systems	PAL / SECAM / NTSC / NTSC4.43 / PAL-M/N
Video Signal	Composite, D-sub 15pin for Component and S-video
Terminal	RCA : Composite video D-sub15 : Component video and S-video input
Computer compatibility	(UXGA/WXGA)/SXGA/XGA/SVGA/VGA/MAC
Terminal	D-sub15 for input, D-sub15 for monitor out
Audio	RCA (L/R) for video input Mini-Jack (stereo) for Computer input Mini-Jack (stereo) for output (variable)
Communication Terminal	Service port (RS-232C)
Presentation Tool	Freeze / Digital Zoom / No Show / etc
Other Feature	Progressive, 3-2 & 2-2 pull down, User Logo
Scanning frequency	H/V sync ~100kHz, ~100Hz Dot clock 110 MHz
Sound output	1.0 W Mono
Fan Noise	XW55 Normal: 30dBA / Eco: 25dBA XW50 Normal: 29dBA / Eco: 24dBA
Voltage	100V-240V AC (auto voltage), 50/60Hz
Dimensions (W x H x D)	330 x 80 x 237 (not including Adjustable Feet)
Weight	2.9kg